

# loyal

## Housed Units Double Concentric Two-Bolt Pillow Block | QAAPL20A315S



Bearing No. QAAPL20A315S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.24                                                                                                                   |
| Housing Construction      | 2.85                                                                                                                   |
| UPC Code                  | 59.0 lb26.8 Kg                                                                                                         |
| Shaft Size Type           | 0883450029506<br>0883450029513<br>0883450029537<br>0883450029544<br>0883450029551<br>0883450029568<br>0883450029575 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-15/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2000 rpm                                                                                                               |
| Shaft Size                | 1200 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | Double Concentric                                                                                                      |