

# loyal

## Housed Units-Double Concentric Two-Bolt Pillow Block | QAASN18A308S



Bearing No. QAASN18A308S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.31                                                                                                                   |
| Housing Construction      | 2.90                                                                                                                   |
| UPC Code                  | 56 lb25.5 Kg                                                                                                           |
| Shaft Size Type           | 0883450351027<br>0883450351034<br>0883450351041<br>0883450351058<br>0883450351065<br>0883450351072<br>0883450351089 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-1/2 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0024 in0.060 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0039 in0.100 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1000 rpm                                                                                                               |
| Pre Install Clearance Max | Double Concentric                                                                                                      |