

# loyal

## Housed Units-Double Concentric Two-Bolt Pillow Block | QAASN22A407S



Bearing No. QAASN22A407S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.06                                                                                                                   |
| Housing Construction      | 2.73                                                                                                                   |
| UPC Code                  | 88 lb40.00 Kg                                                                                                          |
| Shaft Size Type           | 0883450352031<br>0883450352048<br>0883450352055<br>0883450352062<br>0883450352079<br>0883450352086<br>0883450352093 08 |
| Full Timken Part Number   | 0.0050 in0.127 mm                                                                                                      |
| Locking Style             | 4-7/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 1700 rpm                                                                                                               |
| Shaft Size                | 900 rpm                                                                                                                |
| Pre Install Clearance Min | 600 rpm                                                                                                                |
| Pre Install Clearance Max | Double Concentric                                                                                                      |