

# loyal

## Housed Units-Double Concentric Two-Bolt Pillow Block | QAASN26A415S



Bearing No. QAASN26A415S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 3.90                                                                                                                   |
| Housing Construction      | 2.62                                                                                                                   |
| UPC Code                  | 88 lb40.00 Kg                                                                                                          |
| Shaft Size Type           | 0883450352529<br>0883450352536<br>0883450352543<br>0883450352550<br>0883450352567<br>0883450352574<br>0883450352581 08 |
| Full Timken Part Number   | 0.0050 in0.127 mm                                                                                                      |
| Locking Style             | 4-15/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0057 in0.145 mm                                                                                                      |
| Shaft Tolerance           | 1500 rpm                                                                                                               |
| Shaft Size                | 700 rpm                                                                                                                |
| Pre Install Clearance Min | 400 rpm                                                                                                                |
| Pre Install Clearance Max | Double Concentric                                                                                                      |