

# loyal

## Housed Units-Double Concentric Round Flange Block | QAAFY10A200S



Bearing No. QAAFY10A200S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.04                                                                                                                   |
| Housing Construction      | 2.71                                                                                                                   |
| UPC Code                  | 12 lb5.4 Kg                                                                                                            |
| Shaft Size Type           | 0883450021906<br>0883450021913<br>0883450021937<br>0883450021944<br>0883450021951<br>0883450021968<br>0883450021975 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 2 in                                                                                                                   |
| Y2 - Geometry Factor      | 0.040 mm0.0016 in                                                                                                      |
| Y1 - Geometry Factor      | 0.065 mm0.0026 in                                                                                                      |
| Shaft Tolerance           | 4200 rpm                                                                                                               |
| Shaft Size                | 2400 rpm                                                                                                               |
| Pre Install Clearance Min | 1800 rpm                                                                                                               |
| Pre Install Clearance Max | Double Concentric                                                                                                      |