

# Units Double Concentric Four Bolt Square Flange Block | QAAF10A115S



Bearing No. QAAF10A115S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.04                                                                                                                   |
| Housing Construction      | 2.71                                                                                                                   |
| UPC Code                  | 11.0 lb5.0 Kg                                                                                                          |
| Shaft Size Type           | 0883450018500<br>0883450018517<br>0883450018531<br>0883450018548<br>0883450018555<br>0883450018562<br>0883450018579 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 1-15/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0016 in0.040 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0026 in0.065 mm                                                                                                      |
| Shaft Tolerance           | 4200 rpm                                                                                                               |
| Shaft Size                | 2400 rpm                                                                                                               |
| Pre Install Clearance Min | 1800 rpm                                                                                                               |
| Pre Install Clearance Max | Double Concentric                                                                                                      |