

# Units-Double Concentric Four Bolt Square Flange Block | QAAFX18A080S



Bearing No. QAAFX18A080S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.31                                                                                                                   |
| Housing Construction      | 2.90                                                                                                                   |
| UPC Code                  | 42 lb19.1 Kg                                                                                                           |
| Shaft Size Type           | 0883450301060<br>0883450301077<br>0883450301084<br>0883450301091<br>0883450301107<br>0883450301114<br>0883450301121 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 80 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0024 in0.060 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0039 in0.100 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1000 rpm                                                                                                               |
| Pre Install Clearance Max | Double Concentric                                                                                                      |