

# Units-Double Concentric Four Bolt Square Flange Block | QAAFX20A315S



Bearing No. QAAFX20A315S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.23                                                                                                                   |
| Housing Construction      | 2.84                                                                                                                   |
| UPC Code                  | 66 lb29.90 Kg                                                                                                          |
| Shaft Size Type           | 0883450136235<br>0883450136242<br>0883450136259<br>0883450136266<br>0883450136273<br>0883450136280<br>0883450136297 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-15/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2000 rpm                                                                                                               |
| Shaft Size                | 1200 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | Double Concentric                                                                                                      |