

# Bearing Housing Units-Single V-Lock Round Flange Block | QVFY26V407S



Bearing No. QVFY26V407S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 3.90                                                                                                                   |
| Housing Construction      | 2.62                                                                                                                   |
| UPC Code                  | 108.0 lb49.0 Kg                                                                                                        |
| Shaft Size Type           | 0883450045926<br>0883450286251<br>0883450287876<br>0883450287951<br>0883450289399<br>0883450289474<br>0883450290913 08 |
| Full Timken Part Number   | 0.0050 in0.127 mm                                                                                                      |
| Locking Style             | 4-7/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.135 mm0.0053 in                                                                                                      |
| Y1 - Geometry Factor      | 0.170 mm0.0067 in                                                                                                      |
| Shaft Tolerance           | 1500 rpm                                                                                                               |
| Shaft Size                | 700 rpm                                                                                                                |
| Pre Install Clearance Min | 400 rpm                                                                                                                |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |