

# Bearing Housing Units-Double V-Lock Round Flange Block | QVVF28V415S



Bearing No. QVVF28V415S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 3.89                                                                                                                   |
| Housing Construction      | 2.62                                                                                                                   |
| UPC Code                  | 115 lb52.2 Kg                                                                                                          |
| Shaft Size Type           | 0883450369077<br>0883450369084<br>0883450369091<br>0883450369107<br>0883450369114<br>0883450369121<br>0883450369138 08 |
| Full Timken Part Number   | 0.0050 in0.127 mm                                                                                                      |
| Locking Style             | 4-15/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.160 mm0.0063 in                                                                                                      |
| Y1 - Geometry Factor      | 0.201 mm0.0079 in                                                                                                      |
| Shaft Tolerance           | 1200 rpm                                                                                                               |
| Shaft Size                | 650 rpm                                                                                                                |
| Pre Install Clearance Min | 350 rpm                                                                                                                |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |