

# ing Housed Units-Double V-Lock Two-Bolt Pillow Block | QVVSN14V060S



Bearing No. QVVSN14V060S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.32                                                                                                                   |
| Housing Construction      | 2.90                                                                                                                   |
| UPC Code                  | 37.0 lb16.8 Kg                                                                                                         |
| Shaft Size Type           | 0883450177573<br>0883450177764<br>0883450177771<br>0883450178051<br>0883450178242<br>0883450178259<br>0883450205160 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 60 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Shaft Tolerance           | 3050 rpm                                                                                                               |
| Shaft Size                | 1700 rpm                                                                                                               |
| Pre Install Clearance Min | 1400 rpm                                                                                                               |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |