

# ing Housed Units-Double V-Lock Two-Bolt Pillow Block | QVVSN19V303S



Bearing No. QVVSN19V303S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.29                                                                                                                   |
| Housing Construction      | 2.88                                                                                                                   |
| UPC Code                  | 56 lb25.40 Kg                                                                                                          |
| Shaft Size Type           | 0883450149068<br>0883450149075<br>0883450149105<br>0883450149112<br>0883450177672<br>0883450178150<br>0883450205269 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-3/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0043 in0.110 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2200 rpm                                                                                                               |
| Shaft Size                | 1300 rpm                                                                                                               |
| Pre Install Clearance Min | 1000 rpm                                                                                                               |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |