

# ing Housed Units-Double V-Lock Two-Bolt Pillow Block | QVVSN28V500S



Bearing No. QVVSN28V500S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 3.98                                                                                                                   |
| Housing Construction      | 2.67                                                                                                                   |
| UPC Code                  | 88 lb39.9 Kg                                                                                                           |
| Shaft Size Type           | 0883450087346<br>0883450088015<br>0883450099240<br>0883450099677<br>0883450108102<br>0883450108300<br>0883450114936 08 |
| Full Timken Part Number   | 0.0050 in0.127 mm                                                                                                      |
| Locking Style             | 5 in                                                                                                                   |
| Y2 - Geometry Factor      | 0.0063 in0.160 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0079 in0.201 mm                                                                                                      |
| Shaft Tolerance           | 1200 rpm                                                                                                               |
| Shaft Size                | 650 rpm                                                                                                                |
| Pre Install Clearance Min | 350 rpm                                                                                                                |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |