

# loyal Bearing Housing Units-Single Concentric Cartridge Block | QAMC15A212S



Bearing No. QAMC15A212S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 18.000 lb8.2 Kg                                                                                                        |
| Shaft Size Type           | 0883450303224<br>0883450303231<br>0883450303248<br>0883450303255<br>0883450303262<br>0883450303279<br>0883450303286 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 2-3/4 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0020 in0.050 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0031 in0.080 mm                                                                                                      |
| Shaft Tolerance           | 2900 rpm                                                                                                               |
| Shaft Size                | 1600 rpm                                                                                                               |
| Pre Install Clearance Min | 1300 rpm                                                                                                               |
| Pre Install Clearance Max | Single Concentric                                                                                                      |