

# loyal

## ler Bearing Housed Units-Single V-Lock Cartridge Block | QVMC15V208S



Bearing No. QVMC15V208S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 18.000 lb8.2 Kg                                                                                                        |
| Shaft Size Type           | 0883450046329<br>0883450046398<br>0883450207928<br>0883450208079<br>0883450220347<br>0883450220491<br>0883450232777 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 2-1/2 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Shaft Tolerance           | 2900 rpm                                                                                                               |
| Shaft Size                | 1600 rpm                                                                                                               |
| Pre Install Clearance Min | 1300 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |