

# loyal

## ler Bearing Housed Units-Single V-Lock Cartridge Block | QVMC17V215S



Bearing No. QVMC17V215S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.57                                                                                                                   |
| Housing Construction      | 3.07                                                                                                                   |
| UPC Code                  | 26 lb11.80 Kg                                                                                                          |
| Shaft Size Type           | 0883450046527<br>0883450046596<br>0883450207942<br>0883450208093<br>0883450220361<br>0883450220514<br>0883450232791 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 2-15/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1100 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |