

# loyal

## ler Bearing Housed Units-Single V-Lock Cartridge Block | QVMC20V090S



Bearing No. QVMC20V090S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.24                                                                                                                   |
| Housing Construction      | 2.85                                                                                                                   |
| UPC Code                  | 32 lb14.5 Kg                                                                                                           |
| Shaft Size Type           | 0883450046725<br>0883450046794<br>0883450207997<br>0883450208147<br>0883450220415<br>0883450220569<br>0883450232845 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 90 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0043 in0.109 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2000 rpm                                                                                                               |
| Shaft Size                | 1200 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |