

# loyal Bearing Housed Units-Tapered Adapter Cartridge Block | TAMC13K060S



**Bearing No. TAMC13K060S**

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.15                                                                                                                   |
| Housing Construction      | 2.79                                                                                                                   |
| UPC Code                  | 12 lb5.4 Kg                                                                                                            |
| Shaft Size Type           | 0883450084840<br>0883450122689<br>0883450122702<br>0883450122719<br>0883450122726<br>0883450122733<br>0883450122740 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 60 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Shaft Tolerance           | 3200 rpm                                                                                                               |
| Shaft Size                | 1800 rpm                                                                                                               |
| Pre Install Clearance Min | 1500 rpm                                                                                                               |
| Pre Install Clearance Max | Tapered Adapter                                                                                                        |