

# ed Units-Double V-Lock Four Bolt Square Flange Block | QVVFC20V307S



Bearing No. QVVFC20V307S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.23                                                                                                                   |
| Housing Construction      | 2.84                                                                                                                   |
| UPC Code                  | 40.0 lb18.1 Kg                                                                                                         |
| Shaft Size Type           | 0883450065603<br>0883450065610<br>0883450210140<br>0883450210294<br>0883450222570<br>0883450222723<br>0883450235068 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-7/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0043 in0.110 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2000 rpm                                                                                                               |
| Shaft Size                | 1200 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |