

# ed Units-Double V-Lock Four Bolt Square Flange Block | QVVK11V050S



Bearing No. QVVK11V050S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.08                                                                                                                   |
| Housing Construction      | 2.74                                                                                                                   |
| UPC Code                  | 11.0 lb5.0 Kg                                                                                                          |
| Shaft Size Type           | 0883450361262<br>0883450361279<br>0883450361286<br>0883450361293<br>0883450361309<br>0883450361316<br>0883450361323 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 50 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Shaft Tolerance           | 3800 rpm                                                                                                               |
| Shaft Size                | 2200 rpm                                                                                                               |
| Pre Install Clearance Min | 1800 rpm                                                                                                               |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |