

# ing Housed Units-Double V-Lock Two-Bolt Pillow Block | QVVPA20V090S



Bearing No. QVVPA20V090S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.24                                                                                                                   |
| Housing Construction      | 2.85                                                                                                                   |
| UPC Code                  | 65 lb29.50 Kg                                                                                                          |
| Shaft Size Type           | 0883450073011<br>0883450073042<br>0883450208581<br>0883450208734<br>0883450221016<br>0883450221160<br>0883450233446 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 90 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0043 in0.110 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2000 rpm                                                                                                               |
| Shaft Size                | 1200 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |