


# g Housed Units-Single Concentric Two-Bolt Pillow Block | QASN13A207S



Bearing No. QASN13A207S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.15                                                                                                                   |
| Housing Construction      | 2.79                                                                                                                   |
| UPC Code                  | 35 lb15.90 Kg                                                                                                          |
| Shaft Size Type           | 0883450353687<br>0883450353694<br>0883450353700<br>0883450353717<br>0883450353724<br>0883450353731<br>0883450353748 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 2-7/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0016 in0.040 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0026 in0.065 mm                                                                                                      |
| Shaft Tolerance           | 3200 rpm                                                                                                               |
| Shaft Size                | 1800 rpm                                                                                                               |
| Pre Install Clearance Min | 1500 rpm                                                                                                               |
| Pre Install Clearance Max | Single Concentric                                                                                                      |