

# ing Housed Units-Double V-Lock Two-Bolt Pillow Block | QVVPN17V075S



Bearing No. QVVPN17V075S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.57                                                                                                                   |
| Housing Construction      | 3.07                                                                                                                   |
| UPC Code                  | 33 lb15.00 Kg                                                                                                          |
| Shaft Size Type           | 0883450079952<br>0883450079969<br>0883450208260<br>0883450208406<br>0883450220682<br>0883450220835<br>0883450233118 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 75 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1100 rpm                                                                                                               |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |