

# ing Housed Units-Double V-Lock Two-Bolt Pillow Block | QVVPN22V100S



Bearing No. QVVPN22V100S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.06                                                                                                                   |
| Housing Construction      | 2.73                                                                                                                   |
| UPC Code                  | 84 lb38.1 Kg                                                                                                           |
| Shaft Size Type           | 0883450080071<br>0883450080088<br>0883450208321<br>0883450208468<br>0883450220743<br>0883450220897<br>0883450233170 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 100 mm                                                                                                                 |
| Y2 - Geometry Factor      | 0.0053 in0.135 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0067 in0.170 mm                                                                                                      |
| Shaft Tolerance           | 1700 rpm                                                                                                               |
| Shaft Size                | 900 rpm                                                                                                                |
| Pre Install Clearance Min | 600 rpm                                                                                                                |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |