

# loyal

## Bearing Housing Units-Single V-Lock Two-Bolt Pillow Block | QVPL12V203S



Bearing No. QVPL12V203S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.23                                                                                                                   |
| Housing Construction      | 2.84                                                                                                                   |
| UPC Code                  | 17.0 lb7.7 Kg                                                                                                          |
| Shaft Size Type           | 0883450032681<br>0883450096010<br>0883450096447<br>0883450107136<br>0883450107266<br>0883450114004<br>0883450114141 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 2-3/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Shaft Tolerance           | 3500 rpm                                                                                                               |
| Shaft Size                | 2000 rpm                                                                                                               |
| Pre Install Clearance Min | 1650 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |