

# loyal

## Bearing Housing Units-Single V-Lock Two-Bolt Pillow Block | QVPN11V050S



Bearing No. QVPN11V050S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.40                                                                                                                   |
| Housing Construction      | 2.95                                                                                                                   |
| UPC Code                  | 17.0 lb7.7 Kg                                                                                                          |
| Shaft Size Type           | 0883450145176<br>0883450145442<br>0883450151184<br>0883450151337<br>0883450161862<br>0883450162050<br>0883450181310 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 50 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Shaft Tolerance           | 3800 rpm                                                                                                               |
| Shaft Size                | 2200 rpm                                                                                                               |
| Pre Install Clearance Min | 1800 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |