

# loyal Bearing Housed Units-Single V-Lock Two-Bolt Pillow Block | QVPN13V203S



Bearing No. QVPN13V203S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.15                                                                                                                   |
| Housing Construction      | 2.79                                                                                                                   |
| UPC Code                  | 20 lb9.10 Kg                                                                                                           |
| Shaft Size Type           | 0883450145206<br>0883450145541<br>0883450151214<br>0883450151368<br>0883450161893<br>0883450162104<br>0883450181341 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 2-3/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Shaft Tolerance           | 3200 rpm                                                                                                               |
| Shaft Size                | 1800 rpm                                                                                                               |
| Pre Install Clearance Min | 1500 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |