

# loyal Bearing Housed Units-Single V-Lock Two-Bolt Pillow Block | QVPN17V215S



Bearing No. QVPN17V215S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.57                                                                                                                   |
| Housing Construction      | 3.07                                                                                                                   |
| UPC Code                  | 33 lb13.6 Kg                                                                                                           |
| Shaft Size Type           | 0883450057868<br>0883450057967<br>0883450205771<br>0883450205917<br>0883450218191<br>0883450218344<br>0883450230612 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 2-15/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1100 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |