

# loyal

## Bearing Housing Units-Single V-Lock Two-Bolt Pillow Block | QVSN16V070S



Bearing No. QVSN16V070S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 46.0 lb20.9 Kg                                                                                                         |
| Shaft Size Type           | 0883450147378<br>0883450147385<br>0883450147415<br>0883450147422<br>0883450177429<br>0883450177863<br>0883450205030 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 70 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2650 rpm                                                                                                               |
| Shaft Size                | 1500 rpm                                                                                                               |
| Pre Install Clearance Min | 1200 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |