

# ous Units-Single V-Lock Four Bolt Square Flange Block | QVF22V312S



Bearing No. QVF22V312S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 3.80                                                                                                                   |
| Housing Construction      | 2.55                                                                                                                   |
| UPC Code                  | 55 lb24.90 Kg                                                                                                          |
| Shaft Size Type           | 0883450091701<br>0883450091831<br>0883450104685<br>0883450104845<br>0883450110365<br>0883450110648<br>0883450120616 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-3/4 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0043 in0.109 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 1700 rpm                                                                                                               |
| Shaft Size                | 900 rpm                                                                                                                |
| Pre Install Clearance Min | 600 rpm                                                                                                                |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |