

# Used Units-Single V-Lock Four Bolt Square Flange Block | QVFB17V211S



Bearing No. QVFB17V211S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.31                                                                                                                   |
| Housing Construction      | 2.90                                                                                                                   |
| UPC Code                  | 30 lb13.6 Kg                                                                                                           |
| Shaft Size Type           | 0883450149716<br>0883450149839<br>0883450154062<br>0883450154154<br>0883450177153<br>0883450177245<br>0883450187268 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 2-11/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1100 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |