

# Used Units-Single V-Lock Four Bolt Square Flange Block | QVFC20V090S



Bearing No. QVFC20V090S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.23                                                                                                                   |
| Housing Construction      | 2.84                                                                                                                   |
| UPC Code                  | 40.0 lb18.1 Kg                                                                                                         |
| Shaft Size Type           | 0883450041331<br>0883450207690<br>0883450207843<br>0883450220125<br>0883450220279<br>0883450232548<br>0883450232692 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 90 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0043 in0.110 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2000 rpm                                                                                                               |
| Shaft Size                | 1200 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |