

# Used Units-Single V-Lock Four Bolt Square Flange Block | QVFK15V208S



Bearing No. QVFK15V208S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.08                                                                                                                   |
| Housing Construction      | 2.74                                                                                                                   |
| UPC Code                  | 17.0 lb7.7 Kg                                                                                                          |
| Shaft Size Type           | 0883450340229<br>0883450340236<br>0883450340243<br>0883450340250<br>0883450340267<br>0883450340274<br>0883450340281 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 2-1/2 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Shaft Tolerance           | 2900 rpm                                                                                                               |
| Shaft Size                | 1600 rpm                                                                                                               |
| Pre Install Clearance Min | 1300 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |