

# Used Units-Single V-Lock Four Bolt Square Flange Block | QVFX19V080S



Bearing No. QVFX19V080S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.17                                                                                                                   |
| Housing Construction      | 2.80                                                                                                                   |
| UPC Code                  | 35 lb15.90 Kg                                                                                                          |
| Shaft Size Type           | 0883450336741<br>0883450336758<br>0883450336765<br>0883450336772<br>0883450336789<br>0883450336796<br>0883450336802 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 80 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0043 in0.110 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2200 rpm                                                                                                               |
| Shaft Size                | 1300 rpm                                                                                                               |
| Pre Install Clearance Min | 1000 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |