

# ing Housed Units-Double V-Lock Four-Bolt Pillow Block | QVVPK17V300S



Bearing No. QVVPK17V300S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.57                                                                                                                   |
| Housing Construction      | 3.07                                                                                                                   |
| UPC Code                  | 37.0 lb16.8 Kg                                                                                                         |
| Shaft Size Type           | 0883450076845<br>0883450076913<br>0883450209670<br>0883450221955<br>0883450222105<br>0883450234443<br>0883450234597 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 3 in                                                                                                                   |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1100 rpm                                                                                                               |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |