

# ing Housed Units-Double V-Lock Four-Bolt Pillow Block | QVVPK20V304S



Bearing No. QVVPK20V304S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.24                                                                                                                   |
| Housing Construction      | 2.85                                                                                                                   |
| UPC Code                  | 70.0 lb31.8 Kg                                                                                                         |
| Shaft Size Type           | 0883450149488<br>0883450149631<br>0883450153911<br>0883450154000<br>0883450177009<br>0883450177092<br>0883450187039 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-1/4 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0043 in0.109 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2000 rpm                                                                                                               |
| Shaft Size                | 1200 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |