

# Used Units-Single V-Lock Four Bolt Square Flange Block | QVFX22V100S



Bearing No. QVFX22V100S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 3.80                                                                                                                   |
| Housing Construction      | 2.55                                                                                                                   |
| UPC Code                  | 55 lb24.90 Kg                                                                                                          |
| Shaft Size Type           | 0883450337588<br>0883450337595<br>0883450337601<br>0883450337618<br>0883450337625<br>0883450337632<br>0883450337649 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 100 mm                                                                                                                 |
| Y2 - Geometry Factor      | 0.0043 in0.109 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 1700 rpm                                                                                                               |
| Shaft Size                | 900 rpm                                                                                                                |
| Pre Install Clearance Min | 600 rpm                                                                                                                |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |