

# ing Housed Units-Double V-Lock Four-Bolt Pillow Block | QVVPX19V303S



Bearing No. QVVPX19V303S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.29                                                                                                                   |
| Housing Construction      | 2.88                                                                                                                   |
| UPC Code                  | 49.0 lb22.2 Kg                                                                                                         |
| Shaft Size Type           | 0883450371957<br>0883450371964<br>0883450371971<br>0883450371988<br>0883450371995<br>0883450372008<br>0883450372015 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-3/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0043 in0.110 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2200 rpm                                                                                                               |
| Shaft Size                | 1300 rpm                                                                                                               |
| Pre Install Clearance Min | 1000 rpm                                                                                                               |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |