

# ing Housed Units-Double V-Lock Four-Bolt Pillow Block | QVVPX28V130S



Bearing No. QVVPX28V130S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 3.98                                                                                                                   |
| Housing Construction      | 2.67                                                                                                                   |
| UPC Code                  | 136 lb61.70 Kg                                                                                                         |
| Shaft Size Type           | 0883450373647<br>0883450373654<br>0883450373661<br>0883450373678<br>0883450373685<br>0883450373692<br>0883450373708 08 |
| Full Timken Part Number   | 0.0050 in0.127 mm                                                                                                      |
| Locking Style             | 130 mm                                                                                                                 |
| Y2 - Geometry Factor      | 0.0063 in0.160 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0079 in0.201 mm                                                                                                      |
| Shaft Tolerance           | 1200 rpm                                                                                                               |
| Shaft Size                | 650 rpm                                                                                                                |
| Pre Install Clearance Min | 350 rpm                                                                                                                |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |