


# loyal

## Housed Units-Single Concentric Four-Bolt Pillow Block | QAPR15A212S



Bearing No. QAPR15A212S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 27 lb12.2 Kg                                                                                                           |
| Shaft Size Type           | 0883450333245<br>0883450333252<br>0883450333269<br>0883450333276<br>0883450333283<br>0883450333290<br>0883450333306 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 2-3/4 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0020 in0.050 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0031 in0.080 mm                                                                                                      |
| Shaft Tolerance           | 2900 rpm                                                                                                               |
| Shaft Size                | 1600 rpm                                                                                                               |
| Pre Install Clearance Min | 1300 rpm                                                                                                               |
| Pre Install Clearance Max | Single Concentric                                                                                                      |