

# ing Housed Units-Double V-Lock Piloted Flange Cartridge | QVVC22V311S



Bearing No. QVVC22V311S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.06                                                                                                                   |
| Housing Construction      | 2.73                                                                                                                   |
| UPC Code                  | 43 lb19.50 Kg                                                                                                          |
| Shaft Size Type           | 0883450090957<br>0883450091046<br>0883450101950<br>0883450102292<br>0883450109239<br>0883450109369<br>0883450117869 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-11/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0053 in0.135 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0067 in0.170 mm                                                                                                      |
| Shaft Tolerance           | 1700 rpm                                                                                                               |
| Shaft Size                | 900 rpm                                                                                                                |
| Pre Install Clearance Min | 600 rpm                                                                                                                |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |