


# Bearing Housing Units-Single V-Lock Four-Bolt Pillow Block | QVPR16V215S



Bearing No. QVPR16V215S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 27 lb12.2 Kg                                                                                                           |
| Shaft Size Type           | 0883450060011<br>0883450060042<br>0883450114370<br>0883450114417<br>0883450175531<br>0883450204408<br>0883450204729 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 2-15/16 in                                                                                                             |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2650 rpm                                                                                                               |
| Shaft Size                | 1500 rpm                                                                                                               |
| Pre Install Clearance Min | 1200 rpm                                                                                                               |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |