

# Housed Units-Single Concentric Piloted Flange Cartridge | QAC18A304S



Bearing No. QAC18A304S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.31                                                                                                                   |
| Housing Construction      | 2.90                                                                                                                   |
| UPC Code                  | 32 lb14.5 Kg                                                                                                           |
| Shaft Size Type           | 0883450324427<br>0883450324434<br>0883450324441<br>0883450324458<br>0883450324465<br>0883450324472<br>0883450324489 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-1/4 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0024 in0.060 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0039 in0.100 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1000 rpm                                                                                                               |
| Pre Install Clearance Max | Single Concentric                                                                                                      |