

# ing Housed Units-Tapered Adapter Four-Bolt Pillow Block | TAPK15K207S



Bearing No. TAPK15K207S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 29 lb13.20 Kg                                                                                                          |
| Shaft Size Type           | 0883450131070<br>0883450131087<br>0883450131100<br>0883450131117<br>0883450131124<br>0883450131131<br>0883450131148 08 |
| Full Timken Part Number   | 0.0035 in0.089 mm                                                                                                      |
| Locking Style             | 2-7/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.119 mm                                                                                                      |
| Shaft Tolerance           | 0.0017 in0.043 mm                                                                                                      |
| Shaft Size                | 2900 rpm                                                                                                               |
| Pre Install Clearance Min | 1600 rpm                                                                                                               |
| Pre Install Clearance Max | 1300 rpm                                                                                                               |