


# ing Housed Units-Tapered Adapter Four-Bolt Pillow Block | TAPK22K100S



Bearing No. TAPK22K100S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.06                                                                                                                   |
| Housing Construction      | 2.73                                                                                                                   |
| UPC Code                  | 87 lb39.5 Kg                                                                                                           |
| Shaft Size Type           | 0883450084949<br>0883450085014<br>0883450085045<br>0883450085113<br>0883450131872<br>0883450131889<br>0883450131896 08 |
| Full Timken Part Number   | 0.0040 in0.102 mm                                                                                                      |
| Locking Style             | 100 mm                                                                                                                 |
| Y2 - Geometry Factor      | 0.0053 in0.135 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0067 in0.170 mm                                                                                                      |
| Shaft Tolerance           | 0.0025 in0.064 mm                                                                                                      |
| Shaft Size                | 1700 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | 600 rpm                                                                                                                |