

# Used Units Double V-Lock Four Bolt Square Flange Block | QVVF12V203S



Bearing No. QVVF12V203S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.25                                                                                                                   |
| Housing Construction      | 2.86                                                                                                                   |
| UPC Code                  | 14 lb6.4 Kg                                                                                                            |
| Shaft Size Type           | 0883450091879<br>0883450092005<br>0883450104906<br>0883450105095<br>0883450110761<br>0883450111140<br>0883450120784 08 |
| Full Timken Part Number   | 0.0015 in0.038 mm                                                                                                      |
| Locking Style             | 2-3/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0030 in0.075 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0037 in0.094 mm                                                                                                      |
| Shaft Tolerance           | 3500 rpm                                                                                                               |
| Shaft Size                | 2000 rpm                                                                                                               |
| Pre Install Clearance Min | 1650 rpm                                                                                                               |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |