

# Used Units-Double V-Lock Four Bolt Square Flange Block | QVVF16V212S



Bearing No. QVVF16V212S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.48                                                                                                                   |
| Housing Construction      | 3.01                                                                                                                   |
| UPC Code                  | 23 lb10.40 Kg                                                                                                          |
| Shaft Size Type           | 0883450065238<br>0883450065245<br>0883450065252<br>0883450178563<br>0883450178754<br>0883450178945<br>0883450210911 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 2-3/4 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2650 rpm                                                                                                               |
| Shaft Size                | 1500 rpm                                                                                                               |
| Pre Install Clearance Min | 1200 rpm                                                                                                               |
| Pre Install Clearance Max | Double V-Lock                                                                                                          |