

# ing Housed Units-Single V-Lock Piloted Flange Cartridge | QVCW26V110S



Bearing No. QVCW26V110S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 3.90                                                                                                                   |
| Housing Construction      | 2.62                                                                                                                   |
| UPC Code                  | 72 lb32.7 Kg                                                                                                           |
| Shaft Size Type           | 0883450286565<br>0883450286664<br>0883450286749<br>0883450288187<br>0883450288262<br>0883450289702<br>0883450289788 08 |
| Full Timken Part Number   | 0.0050 in0.127 mm                                                                                                      |
| Locking Style             | 110 mm                                                                                                                 |
| Y2 - Geometry Factor      | 0.0053 in0.135 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0067 in0.170 mm                                                                                                      |
| Shaft Tolerance           | 1500 rpm                                                                                                               |
| Shaft Size                | 700 rpm                                                                                                                |
| Pre Install Clearance Min | 400 rpm                                                                                                                |
| Pre Install Clearance Max | Single V-Lock                                                                                                          |