

# loyal

## g Housing Units-Tapered Adapter Piloted Flange Cartridge | DVC15K065S



**Bearing No. DVC15K065S**

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 18.000 lb8.2 Kg                                                                                                        |
| Shaft Size Type           | 0883450004121<br>0883450004138<br>0883450004152<br>0883450004169<br>0883450004176<br>0883450004183<br>0883450004190 08 |
| Full Timken Part Number   | 0.0035 in0.089 mm                                                                                                      |
| Locking Style             | 65 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0037 in0.095 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0047 in0.120 mm                                                                                                      |
| Shaft Tolerance           | 2900 rpm                                                                                                               |
| Shaft Size                | 1600 rpm                                                                                                               |
| Pre Install Clearance Min | 1300 rpm                                                                                                               |
| Pre Install Clearance Max | Tapered Adapter                                                                                                        |