

# g Housed Units-Tapered Adapter Piloted Flange Cartridge | DVC20K307S



**Bearing No. DVC20K307S**

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.24                                                                                                                   |
| Housing Construction      | 2.85                                                                                                                   |
| UPC Code                  | 37.0 lb16.8 Kg                                                                                                         |
| Shaft Size Type           | 0883450004824<br>0883450004831<br>0883450004855<br>0883450004862<br>0883450004879<br>0883450004886<br>0883450004893 08 |
| Full Timken Part Number   | 0.0040 in0.102 mm                                                                                                      |
| Locking Style             | 3-7/16 in                                                                                                              |
| Y2 - Geometry Factor      | 0.0043 in0.110 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0055 in0.140 mm                                                                                                      |
| Shaft Tolerance           | 2000 rpm                                                                                                               |
| Shaft Size                | 1200 rpm                                                                                                               |
| Pre Install Clearance Min | 900 rpm                                                                                                                |
| Pre Install Clearance Max | Tapered Adapter                                                                                                        |